



Nails Specification

Head Dia	5.8~6.2mm	
Shank	Dia	0.099"(2.50mm),0.113"(2.87mm)
Shank Type	Smooth, Ring, Screw	
Point	DP, BDP, TBP, BCP, CP	
Finish	Bright, Coation, Electrc Galv.	
Length	1¾"(45mm), 2"(50mm), 2¼(57mm), 2½(64mm), 3"(75mm)	
PcsxCoil/CTN	300x30, 250x20	
Purpose	Siding, Sheathing, Decking, Subfloors,	

Exterior Trim, Fencing & Wood Shingles



Nails Specification

Head Dia	4.8~5.2mm	
Shank	Dia	0.083"(2.10mm),0.092"(2.30mm)
Shank Type	Smooth, Ring, Screw	
Point	DP, BDP, TBP, BCP, CP	
Finish	Bright, Coation, Electrc Galv.	
Length	1"(25mm), 1¼"(32mm), 1½"(38mm), 1¾"(45mm), 2"(50mm)	
PcsxCoil/CTN	400x40 , 350x40	
Purpose		

Sheathing, Decking, Subfloors, Exterior Decks,
Pallets/Pallet Repair, Crate & Box Assembly



Nails Specification
4" (Purpose) CTN

0.27"(2.0mm) 0.131"(3.30mm)
Framing, Sheathing, Decking, Subfloors, Exterior Decks, Pallets, Pallet Repair